

RSFA 973100-11

FEB 3 2001



U.S. Department
of Transportation
Research and
Special Programs
Administration

DEPT. OF TRANSPORTATION
RECEIVED
00 FEB 14 PM 4:25

400 Seventh Street, S.W.
Washington, D.C. 20390

DOT-E 11993
(SECOND REVISION)

EXPIRATION DATE: December 31, 2001

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: Breed Technologies, Incorporated
Lakeland, FL

2. a. PURPOSE AND LIMITATIONS: This exemption authorizes the manufacture, marking and sale of non-DOT specification cylinders (pressure vessels) for use as components of automobile vehicle safety systems. This exemption provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein.

b. FIVE YEAR TRANSPORTATION AUTHORIZATION: This exemption authorizes transportation of the pressure vessels identified herein for up to five years from the date of manufacture. This exemption provides no certification of safety for end use environments and life cycles.

c. EXEMPTION SCOPE LIMITATIONS: This exemption only applies to a package when it is an article of commerce in transportation. The safety analyses performed in development of this exemption only considered the hazards and risks associated with transportation in commerce. The safety analyses did not consider the hazards and risks associated with consumer use, incorporation as a component of a vehicle or other device, or other uses not associated with transportation in commerce.

3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.

4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR §§ 173.301(h) and 173.302 insofar as a non-DOT specification cylinder is not authorized; § 178.65(f)(1) insofar as the hold time at test pressure must be a minimum of 10 seconds.
5. BASIS: This exemption is based on the application of Breed Technologies, Inc. dated November 16, 1999, submitted in accordance with § 107.105 and the public proceeding thereon and § 107.109.
6. HAZARDOUS MATERIALS (49 CFR § 172.101) :

Hazardous materials description -- proper shipping name	Hazard Class/ Division	Identification Number	Packing Group
Non-toxic, non-liquefied gases and mixtures thereof/ Proper shipping name as specified in 49 CFR § 172.101	2.1, or 2.2 as appropriate	As appropriate	N/A

A vehicle safety system or component which contains a quantity of pyrotechnic materials must be classed and approved as provided for in § 173.56 of the HMR. If the pyrotechnic material augments the volume of the gas in the pressure vessel, or in any way enhances the performance of the compressed gas, the device must be tested in the same configuration as when shipped.

7. SAFETY CONTROL MEASURES: Packaging prescribed is a non-DOT specification pressure vessel meeting the drawings on file with the Office of Hazardous Materials Exemptions and Approvals (OHMEA) and the following requirements:

a. PACKAGING -

(1) The maximum service pressure at 70°F may not exceed 6,000 psig. The minimum test pressure is the pressure of the contents at 200°F. The rated service

pressure may not exceed 80 percent of the test pressure and the water volume of each pressure vessel may not exceed one liter.

(2) Material of construction must conform to all requirements of § 178.65(b), except that aluminum is limited to 6061 alloy of T6 temper.

(3) Manufacturing requirements must conform to all requirements of § 178.65(c).

(4) The minimum wall thickness must be such that the wall stress meets the requirements of § 178.65(d).

(5) Openings and attachments must conform to all requirements of § 178.65(e) except that a fill port hole of up to 0.130 inch in diameter may be located in an imaginary circle, concentric to the axis of the cylinder, not exceeding 90 percent of the outside diameter of the cylinder. Drawings showing the location of the fill port hole must be on file with the OHMEA.

(6) Each pressure vessel must be equipped with a pressure relief device designed to meet all the requirements for a rupture disk prescribed in the Compressed Gas Association (CGA) Pamphlet S-1.1. The pressure relief device shall be capable of preventing rupture of the pressure vessel when subjected to fire test conducted in accordance with CGA Pamphlet C-14.

(7) Pressure vessels, components, and vehicle safety systems must be transported in strong outside packaging in accordance with § 173.301(k).

b. TESTING -

(1) Each pressure vessel must be tested as required in § 178.65(f) except that the hold time at test pressure specified in § 178.65(f)(1) must be no less than 10 seconds.

(2) The flattening test specified in § 178.65(g) is required, except that the wedge radius prescribed in paragraph (g) (3) may not exceed 1.5 inches for aluminum pressure vessels having a wall thickness exceeding 0.25 inch.

(3) A representative vehicle safety system, packaged as it would be for shipment, must be activated and no materials other than non-toxic, non-flammable vapors or gases may be expelled from the package.

c. MARKING - Each pressure vessel must be durably marked as follows:

DOT-E 11993/6000¹

Lot No. xxxxx²

Manufacturer's Name

The Pressure Vessel May Not Be Refilled

¹ Where 6000 represents the design service pressure.

² Where xxxxx is the lot number as appropriate.

NOTE: Each line of these markings may be placed without regard to location or order on the pressure vessel.

8. SPECIAL PROVISIONS:

a. This exemption is limited to pressure vessels used as components of a vehicle safety system. The pressure vessels are excepted from the requirements of the HMR, Part 178 when the design has been certified by an Independent Inspection Agency, approved under § 173.300a, as having met all the requirements of this exemption.

b. The Independent Inspection Agency's design certification must include test results and documents related to explosive classification and approval. A copy of the certification must be maintained at each facility where the vehicle safety system is manufactured and by the Independent Inspection Agency for a period of 15 years from the date of completion of the design certification.

c. In accordance with the provisions of Paragraph (b) of § 173.22a, persons may use the packaging authorized by this exemption for the transportation of the hazardous materials specified in paragraph 6, only in conformance with the terms of this exemption.

d. A person who is not a holder of this exemption, but receives a package covered by this exemption, may reoffer it

for transportation provided no modifications or changes are made to the package and it is offered for transportation in conformance with this exemption and the HMR.

e. A current copy of this exemption must be maintained at each facility where the package is offered or reoffered for transportation.

f. A current copy of this exemption must be maintained at each facility where the package is manufactured under this exemption. It must be made available to a DOT representative upon request.

g. No modifications may be made to the pressure vessel, pyrotechnic components or production vehicle safety system which would affect the performance of the vehicle safety system or its compliance with the requirements of this exemption until such modifications have been reviewed, tested and certified by an Independent Inspector as meeting the requirements of this exemption.

h. This exemption is to serve as an authorization of The Competent Authority for the United States (CA-9804002) issued in accordance with the General Packing Instructions Part 3, Chapter 2, Paragraph 2.5 of the International Civil Aviation Organization Technical Instructions (ICAO TI) and additionally meets the requirements of State Variation US 6. Pressure vessels or vehicle safety systems complying with this exemption are authorized to be shipped pursuant to Packaging Instruction 200 of ICAO TI.

9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle, rail freight, cargo vessel, and cargo aircraft only.
10. MODAL REQUIREMENTS: A current copy of this exemption must be carried aboard each cargo vessel or aircraft used to transport packages covered by this exemption. The shipper shall furnish a copy of this exemption to the air carrier before or at the time the shipment is tendered.
11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this exemption and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:
 - o All terms and conditions prescribed in this exemption and the Hazardous Materials Regulations, Parts 171-180.
 - o Registration required by § 107.601 et seq., when applicable.


- o All terms and conditions prescribed in this exemption and the Hazardous Materials Regulations, Parts 171-180.
- o Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this exemption must receive training on the requirements and conditions of this exemption in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this exemption, including display of its number, when this exemption has expired or is otherwise no longer in effect.

12. REPORTING REQUIREMENTS: The carrier is required to report any incident involving loss of packaging contents or packaging failure to the Associate Administrator for Hazardous Materials Safety (AAHMS) as soon as practicable. (Sections 171.15 and 171.16 apply to any activity undertaken under the authority of this exemption.) In addition, the holder(s) of this exemption must also inform the AAHMS, in writing, as soon as practicable of any incidents involving the package and shipments made under this exemption.

Issued in Washington, D.C.



 Robert A. McGuire
 Acting Associate Administrator for
 Hazardous Materials Safety

FEB 3 2000

 (DATE)

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Research and Special Programs Administration, Department of Transportation, Washington, D.C. 20590.
 Attention: DHM-31.

The original of this exemption is on file at the above office. Photo reproductions and legible reductions of this exemption are permitted. Any alteration of this exemption is prohibited.

Copies of exemptions may be obtained from the AAHMS, U.S. Department of Transportation, 400 7th Street, S.W., Washington, DC 20590-0001, Attention: Records Center, 202-366-5046.

Dist: FHWA, FRA, FRA, USCG
 PO: SS